

## Versatile nutrient management with the Litter-Lime Spreader



## Specifications

|   |                          |
|---|--------------------------|
| Struck Level ASAE S324.1                      | 461 cu. ft.              |
| Heaped ASAE S324.1                            | 748 cu. ft.              |
| Load carrying capacity                        | 16 tons                  |
| Depth of box, inside                          | 43"                      |
| Width of box, inside                          | 48" / 95"                |
| Length of box, inside                         | 22' 8"                   |
| Overall width w/ flotation tires, 550/60-22.5 | 9' 9"                    |
| Overall width w/ flotation tires, 710/50-26.5 | 10' 9"                   |
| Overall height                                | 8' 9"                    |
| Overall length                                | 31' 4"                   |
| Loading height                                | 8' 1"                    |
| Spinner speed                                 | 420 RPM                  |
| Fan diameter                                  | 35.5"                    |
| Number of spinners                            | 2                        |
| Number of paddles per spinner                 | 6                        |
| Tractor PTO HP (min. recommended)             | 150 HP                   |
| Number of unloading speeds                    | Infinite from 0-19'/min. |
| PTO speed                                     | 1000                     |
| PTO shaft diameter                            | 1 3/8" (1 3/4")          |
| Endgate cylinders                             | 2                        |


Steel Box | Poly Board Flooring | Precision Application Options  
Heavy-Duty Pintle Chain | Guillotine Metering Endgate | Engineered Spinners



**748**  
cu. ft. heaped



**16 TON**  
load capacity



**8' 1"**  
loading height



**150 HP**  
min. tractor PTO